



# TITAN 600

The Titan 600 is a versatile 2 Deck Tracked Scalping Screen, in a compact footprint, with the capacity to screen up to 280tph (308 US tph) depending on the application.

The Titan 600 can be rapidly switched between a 2-way and 3-way split unit making it a highly versatile machine suitable for a range of applications.

Previously known as the Warrior 600, this machine brings with it a high pedigree & industry reputation which will undoubtedly continue to grow.



## ✓ APPLICATIONS

### AGGREGATE



Sand & gravel  
Blasted rock  
River rock

### RECYCLING



Top Soil  
C&D waste  
Composed materials  
Wood By-Products  
Overburden  
Foundry Waste

### MINING



Processed ores  
Processed minerals



## TECHNICAL HIGHLIGHTS



- High capacity output up to 280tph (308 US tph) from a compact footprint



- Versatile unit for 3-way or 2-way splitting, stockpiling or scalping before or after a crusher
- Heavy duty 2.49m x 1.17m (8' 2" x 3' 10") single shaft incline screenbox with adjustable stroke



- Smart design minimises weight but retains strength and robustness
- Rapid conversion from 3 way split to 2-way split



- Ultra-low fuel consumption with optimised hydraulics
- Fits inside a 40' shipping container to simplify the transport process



# TECHNICAL SPECIFICATION



## 1 FEEDER/HOPPER

1000mm wide (40") heavy duty belt feeder  
Hopper Capacity: 3m<sup>3</sup> (3.9 cu. yd)  
Fold down rear door for crusher feeding

## 2 SCREENBOX

Heavy Duty 2.49m x 1.17m (8' 2" x 3' 10") 2 deck screen  
Highly aggressive screen drive  
2 bearing shaft with Direct Drive system

## 3 OVERSIZE TAIL CONVEYOR

1000mm (40") wide  
2.7m (8' 10") stockpile height  
Impact slips along feedboot  
Variable speed control

## 4 FINE SIZE SIDE CONVEYOR

650mm (26") wide  
2.9m (9' 6") stockpile height  
Hydraulically folding

## 5 MIDSIZE SIDE CONVEYOR

650mm (26") wide  
2.8m (9' 2") stockpile height  
Hydraulically folding

## 6 POWER UNIT

Tier 3: Deutz D2011 L04I 36.4kW (48.8hp) @2300rpm  
Tier 4F: Deutz TD2.9L4 42kW (56.3hp) @2200rpm  
Stage V: Deutz TD2.9 45kW (60hp) @2200rpm  
Fuel Tank: 145L (38 US Gal)



# DIMENSIONS

## WORKING



## TRANSPORT

Length: 10.98m (36')  
Width: 2.25m (7' 5")  
Height: 2.55m (8' 4")

## WEIGHT

Total Weight: 12,780kg (28,175 lbs)

## GET IN TOUCH

**Dungannon**  
200 Coalisland Road, Dungannon,  
Co Tyrone, BT71 4DR, Northern Ireland  
Tel: +44 (0) 28 87 718 500  
Fax: +44 (0) 28 87 747 231

**Louisville**  
11001 Electron Drive,  
Louisville, Kentucky, 40299 USA  
Tel: +1 502 736 5200  
Fax: +1 502 736 5202



[www.powerscreen.com](http://www.powerscreen.com)

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2023 Terex GB Limited. Published and Printed in July 2023.